

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11) EP 1 014 145 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:  
28.06.2000 Bulletin 2000/26

(51) Int. Cl.<sup>7</sup>: G02B 26/12, G06K 15/12,  
H04N 1/04

(21) Application number: 99204236.6

(22) Date of filing: 10.12.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(30) Priority: 22.12.1998 US 218508

(71) Applicant: EASTMAN KODAK COMPANY  
Rochester, New York 14650 (US)

(72) Inventor:  
Hoeft, Jon L.,  
Eastman Kodak Company  
Rochester, New York 14650-2201 (US)

(74) Representative:  
Nunney, Ronald Frederick Adolphe et al  
Kodak Limited,  
Patents, W92-3A,  
Headstone Drive  
Harrow, Middlesex HA1 4TY (GB)

(54) Method and apparatus for determining the starting position and the power of a scanning light beam to be used in writing on a media

(57) A method and apparatus for determining a line start writing position of a scanning light beam in a scanning light beam writing system. A first detector and a second detector are positioned in the scan path of the scanning light beam for detection of the scanning light beam. The information obtained from the detector is used to determine the line start for commencing writing on a media and for monitoring and controlling the power level of the scanning light beam.




FIG. 1

BEST AVAILABLE COPY

EP 1 014 145 A2

## Description

**[0001]** The present invention is directed to an apparatus, which uses a scanning light beam, such as a laser light beam, for writing onto a media.

**[0002]** In devices for writing onto media using a scanning light beam it is important to know when to turn on and start writing with the scanning light beam. In a typical prior art scanning writing apparatus, a laser light beam or other illuminated light, is directed to a rotating polygon having a plurality of mirror facets which direct the light beam onto a media. Each facet is used to write a successive line of data. These type of systems have the disadvantage of relying on ill-defined specifications for rotating stability of the polygon. Additionally, accumulative error in timing from the first facet to the last facet may occur. Thus, there is a need to provide appropriate timing for line start for each successive facet.

**[0003]** It is also important to maintain a predetermined intensity level of the writing beam. As is typical with writing beams, such as laser beams, over time the intensity can vary, which can affect the overall quality of the writing apparatus. Most systems monitor light beams in the static mode, that is, before scanning. Monitoring may be done right at the output of the laser, or after the acoustic optical modulator (AOM) or attenuator. A hand-held light meter can periodically be inserted into the beam for measuring of the intensity. The problem is that measuring the intensity at these positions does not actually reflect the amount of light that will be hitting the media plane, which may result in erroneous measurements. The intensity of the beam should be measured as close to the writing plane as possible in order to account for all possible attenuation. Another prior art method used to monitor the intensity is to scan and print an image onto photosensitive material media, for example, photographic paper, then develop the paper and then measure the results of the developed paper with a densitometer. This is a tedious and time-consuming process.

**[0004]** The present invention provides a method for accurately determining a line start for each facet and also provides a method of measuring the light beam amplitude automatically and as close to the focal plane of the media as possible.

**[0005]** The present invention is directed to overcoming one or more of the problems set forth above. Briefly summarized according to one aspect of the present invention, there is provided a method of determining a line start writing position of a scanning light beam in a scanning light beam writing system, the writing system having a scanning light beam which projects along a scan path on a writing plane from a start position to an end position, a first detector and a second detector positioned in the scan path for detection of the scanning light beam as it is scanned along the scan path for detection of the light beam, the second detector being spaced a predetermined distance from the first

detector at a point after the scanning light beam passes the first detector, the method comprising the steps of:

moving the scanning light beam at a known velocity along the scan path from the start position to the end position;

monitoring a first output parameter of the first detector produced by the scanning light beam passing over the first detector;

monitoring a second output parameter of the second detector produced by scanning light beam passing over the second detector;

noting a reference point when the parameter measured by the first and second detectors reach a predetermined relationship; and

determining the line start position on the scan path for start of writing by the scanning light beam based on the reference point.

**[0006]** In accordance with another aspect of the present invention there is provided an apparatus for writing onto a media using a scanning light beam, comprising:

a scanning light beam for projecting a scanning path on a writing plane for receiving a photosensitive media for writing thereon, the scanning path having a start position and an end position;

a first detector positioned in the scan path after the start position for detection of the scanning light beam;

a second detector positioned in the scan path at a point after the first detector for detection of the light beam, the second detector being spaced a predetermined distance from the first detector, the first and second detectors producing an output signal in response to the scanning light beam passing over the first and second detectors;

means for noting a reference point when a particular relationship occurs between the value of the output signals produced by the first and second detectors; and

means for generating a line start signal in response to the reference point and for commencing writing with the scanning light beam based on the photosensitive media.

**[0007]** In accordance with yet another aspect of the present invention there is provided a method of monitoring and/or calibrating a writing system, the writing system having a scanning light beam which projects along a scan path having a start position and an end position on a writing plane, a first detector positioned in the scan path for detecting the scanning light beam and a second detector positioned after the first detector in the scanning path for detection of the light beam, the second detector being spaced a predetermined distance from the first detector, the method comprising the steps of:

turning on a scanning light beam and moving the scanning light beam at a known velocity along the scanning path at a first power level;  
 monitoring a first output signal measured by the first detector in response to the scanning light beam passing over the first detector;  
 noting a reference position when the first output signal reaches a predetermined value and generating a pulse signal based on the reference position;  
 changing the power level of the scanning beam to a predetermined second level in response to the reference position;  
 measuring a second output signal measured by the second detector in response to the light beam passing over the second detector; and comparing the second output signal of the scanning light beam with respect to a predetermined reference value and making an adjustment to the power level of the scanning light beam in accordance with the predetermined value.

[0008] In still another aspect of the present invention there is provided a scanning light beam writing apparatus, comprising:

a scanning light beam which projects along a scan path having a start position and an end position on a writing plane;  
 a first detector positioned in the scan path producing a first output signal in response to the scanning light beam passing over the first detector; a second detector positioned after the first detector in the scanning path for producing a second output signal in response to the scanning light beam passing over the second detector, the second detector being spaced a predetermined fixed distance from the first detector;  
 means for monitoring the first output signal produced by the first detector as the scanning light beam passes over the first detector;  
 means for noting a reference position when the first output signal reaches a predetermined value and generating a pulse signal based on the reference position;  
 means for changing the power level of the scanning beam to a predetermined second level in response to the reference position;  
 means for measuring the second output signal produced by the second detector when the scanning light beam passes over the second detector;  
 means for comparing the value of the second signal of the second detector with respect to a predetermined reference value; and  
 means for adjusting the power level of the scanning light beam in accordance with the predetermined value.

[0009] The above, and other objects, advantages

and novel features of the present invention will become more apparent from the accompanying detailed description thereof when considered in conjunction with the following drawings.

[0010] In the detailed description of the preferred embodiments of the invention presented below, reference is made to the accompanying drawings in which:

Fig. 1 is a schematic view of a writing apparatus made in accordance with the present invention;

Fig. 2 is a diagrammatic representation illustrating the sensors used for monitoring the scanning light beam for determining line start and respective time lines for various signals associated therewith as a function of time; and

Fig. 3 is a diagrammatic representation illustrating the detectors used for monitoring the power level of the scanning light beam and various signals associated therewith as a function of time.

[0011] The present description will be directed in particular to elements forming part of, or in cooperation more directly with, the apparatus in accordance with the present invention. It is understood that elements not specifically shown or described may take various forms well known to those skilled in the art.

[0012] The present description will be directed in particular to elements forming part of, or in cooperation more directly with, the apparatus in accordance with the present invention. It is understood that elements not specifically shown or described may take various forms well known to those skilled in the art.

[0013] Referring to Fig. 1, there is illustrated a scanning apparatus 10 made in accordance with the present invention. The apparatus 10 includes a light source for producing a beam of light for writing onto a media 12. In the particular embodiment illustrated, the light source is a laser 14, which produces a writing light beam 16, which is directed to a rotating polygon 18 having a plurality of mirror facets 20 for reflecting of the light beam onto a writing path 22 having a starting point A and an ending point B. As is typical with such scanning apparatuses, an acoustic optical modulator 24 and attenuator 26 are used to provide digital data for writing of images onto the media 12. An f- $\theta$  lens 28 is provided for properly focusing of the beam onto the writing plane 30 over which the photosensitive media 12 passes. A controller 31 having appropriate circuit boards in conjunction with a computer 33 is provided for controlling operation of apparatus 10 as is customarily done in similar type devices. An appropriate mechanism, not shown, is provided for moving media 12 past writing path 22 for allowing the scanning light beam to write successive lines of digital image data on media 12 as is customarily done in such devices. In the particular embodiment illustrated, the photosensitive media 12 is photographic paper. However, it is to be understood that the photosensitive media 12 may be any other type of media on which the

scanning light beam may be used for writing. For example, but not by way of limitation, photographic film, thermal paper and sharable surface used in electrostatic writing.

[0014] As illustrated in Fig. 1, a pair of detectors 32,34 are provided in the writing path 22 of the scanning light beam 16 spaced apart a fixed distance D. As can be seen, the detectors 32,34 are positioned after point A where the lighting beam first starts its scanning, but prior to the actual line start position C used for initiating writing onto the media 12. In the particular embodiment illustrated, the detectors 32,34 each comprise a photodiode, which produce a signal in response to the scanning light beam 16 passing thereover. Preferably, the two detectors 32,34 are provided in the same supporting structure so that the distance D can be precisely controlled, which plays an important element in determining the line start position C for initiating writing onto the photosensitive media 12. In the particular embodiment illustrated, the photodetectors 32,34 are provided in a single SPOT-2DM1 detector, which may be purchased from UDT Sensors, Inc. However, it is to be understood that detectors 32,34 may be of any desired construction or manufacture so long as they are capable of producing the appropriate signals in response to the scanning passing thereover as discussed later herein.

[0015] Referring to Fig. 2, there is illustrated in diagrammatic fashion detectors 32,34 and how the scanning light beam 16 passes thereover and the various signals produced. As can be seen, the scanning light beam 16 starts at point A and travels in the direction indicated by arrow 36 across detectors 32,34. The circles indicated by T0-T9 represent the position and intensity of the beam as it passes detectors 32,34. The time line 38 merely represents the timing sequence of the scanning beam 16 as it passes detectors 32,34 along writing path 22. Line 40 indicates the amplitude of the light beam as it starts from point A as it progresses by the detectors 32,34. Lines 42,44 each represent the output voltage of each of detectors 32,34, respectively, in relationship to the light beam 16 traveling along writing path 22. The two lines 42,44 use the same zero reference for the output voltage. As can be seen, the voltage output of detector 32 increases from approximately T1 to a maximum at point at T2 while the output voltage of detector 34 is zero at T2. As the scanning light beam 16 passes the first detector 32 at T3, the voltage output of the detector 32 begins to decrease. However, at about this point, or shortly thereafter, as indicated by line 44, the voltage output of detector 34 begins to increase in response to the scanning light beam 16. At point 46 it can be seen that the two lines 42,44 cross. This cross-over represents that the output voltage of both detectors 32,34 are the same. At point 45 a line start signal is generated. It is to be understood that the determining of when the line signal based on the cross-over point 45 is generated can be accomplished in any desired manner. In the particular embod-

iment illustrated, a simple comparator in controller 31 is used for comparing the signals of the outputs of detectors 32,34, thus when the two signals are substantially the same, an output signal 49 is produced. This is used to begin line start at point C. However, as indicated by line 40, a short time period after point 46, the power to the scanning light beam 16 is turned off and then turned back on at point C as determined by a predetermined time period T, which has been preselected, which is based on output signal 49. Because the detectors 32,34 are fixed in relationship to each other, the point 46 at which the voltage output signal of the detectors cross will be substantially at the same point each time the scanning light beam 16 is passed over the detectors. Thus, there is provided a line signal start which can be reliably repeated for use in determining the point for initiating lighting of the laser light beam as indicated by point C. The laser, at point C, is turned on to the appropriate level and the appropriate digital data is fed through the AOM 24 for writing on media 12. It is, of course, understood that the laser light beam 16 may be turned on just prior to the time point C, the time at which digital data is provided for modulating of the light beam 16 and actual writing commences.

[0016] Referring to Fig. 3, there is illustrated a diagrammatic representation similar to Fig. 2, like numerals indicating like parts and sequences. Fig. 3 illustrates how the intensity of the scanning light beam 62 can be monitored and controlled accurately during each scan and at the writing plane 30 of the media 12. When the light beam 16 is detected by detector 32, the output signal begins to increase in amplitude as indicated by numeral 53. The output signal being directly related to the power level of the laser 14, thus the power level of laser can be readily determined. If the detector was previously calibrated to a standard source, the absolute power level of the laser could be determined. When the output signal passes through a threshold VT, a signal LE1 is generated using a comparative circuit provided in controller 31. Then a control circuit, also provided in controller 31, senses the LE1 signal and the intensity of light beam 16 is changed to an amplitude A2 at a time delay of Td1 after the circuit senses that threshold VT has been reached. A track and hold circuit is provided in controller 31 for monitoring the voltage of detector 32 and holding it a certain length of time after a predetermined time period Td2 after VT. By this time, the amplitude of the laser 14 has been lowered to amplitude A2. An A/D clock in controller 31, using the appropriate clock scheme, takes the voltage as determined by the track and hold circuit so as to convert the analog voltage to a digital value for later processing. Thus, the amplitude of the second detector 34 is captured which can be compared with the power measurement levels previously obtained for the scanning light beam 16, and if power measurement level has changed, appropriate control of the light beam 16 may be adjusted. For example, if over time the measured amplitude of the laser has

been reduced, the power to the laser 14 is increased appropriately to the desired power level. If the measured power level, as obtained by the output signal of sensor 34, is too high, appropriate reduction in power level is made. The present invention, however, can automatically take power measurements during each scan, compare it to prescribed limits and appropriate adjustments may be made.

[0017] In the preferred embodiment illustrated, the output current of the detectors was converted to a voltage and monitored. However, the present invention is not so limited. However, if desired, a different output parameter of the detectors 32,34 may be monitored, for example, but not by way of limitation, the output current of the detectors may be monitored directly. Thus, when the value of the current for both detectors reach the same value the line start signal can be generated as previously discussed.

[0018] Also, the present invention is not limited with respect to the relation that the voltage (or current) of the detectors may be the same. For example, but not by way of limitation, when the voltage of the second detector is one-half of the first voltage, some other relationship can be used for determining the line start signal.

## Claims

1. A method of determining a line start writing position of a scanning light beam in a scanning light beam writing system, said writing system having a scanning light beam which projects along a scan path on a writing plane from a start position to an end position, a first detector and a second detector positioned in said scan path for detection of said scanning light beam as it is scanned along said scan path for detection of said light beam, said second detector being spaced a predetermined distance from said first detector at a point after said scanning light beam passes said first detector, the method comprising the steps of:

moving said scanning light beam along said scan path from said start position to the end position;

monitoring a first output parameter of said first detector produced by said scanning light beam passing over said first detector;

monitoring a second output parameter of said second detector produced by said scanning light beam passing over said second detector;

noting a reference point when said parameter measured by said first and second detectors reach a predetermined relationship; and determining the line start position on said scan path for start of writing by said scanning light beam based on said reference point.

2. A method according to claim 1 wherein said first

and second parameters comprises the current measured by said first and second detectors.

3. A method according to claim 1 wherein said first and second parameters comprises the voltage measured by said first and second detectors.

4. A method according to claim 1 wherein said predetermined relationship comprises the point at which said first and second measured parameters are substantially the same.

5. A method according to claim 4 wherein a line of digital data is started in accordance with the line start position previously determined and said scanning light beam is turned off after completion of the writing of said line of digital data.

6. An apparatus for writing onto a media using a scanning light beam, comprising:

a scanning light beam for projecting a scanning path on a writing plane for receiving a photosensitive media for writing thereon, said scanning path having a start position and an end position;

a first detector positioned in said scan path after said start position for detection of said scanning light beam;

a second detector for positioning in said scan path at a point after said first detector for detection of said light beam, said second detector being spaced a predetermined distance from said first detector, said first and second detectors producing an output signal in response to said scanning light beam passing over said first and second detectors;

means for noting a reference point when a particular relationship occurs between the value of said output signals produced by said first and second detectors; and

means for generating a line start signal in response to said reference point and for commencing writing with said scanning light beam based on said photosensitive media.

7. An apparatus according to claim 6 wherein said output signal measured by said first and second detectors in response to said light beam passing over said detectors comprises the voltage or current produced by said first and second detectors.

8. An apparatus according to claim 6 further comprising a controller for turning on said scanning light beam for writing on said media in accordance with the line start position previously determined and for turning off said scanning light beam after completion of the writing of said line of digital data.

9. A method of monitoring and/or calibrating a writing system, said writing system having a scanning light beam which projects along a scan path having a start position and an end position on a writing plane, a first detector positioned in said scan path for detecting said scanning light beam and a second detector positioned after said first detector in said scanning path for detection of said light beam, said second detector being spaced a predetermined distance from said first detector, said method comprising the steps of:


turning on a scanning light beam and moving said scanning light beam along said scanning path at a first power level;  
 monitoring a first output signal measured by said first detector in response to said scanning light beam passing over said first detector;  
 noting a reference position when said first output signal reaches a predetermined value and generating a pulse signal based on said reference position;  
 changing the power level of said scanning beam to a predetermined second level in response to said reference position;  
 measuring a second output signal measured by said second detector in response to said light beam passing over said second detector;  
 comparing the said second output signal of said scanning light beam with respect to a predetermined reference value and making an adjustment to the power level of said scanning light beam in accordance with said predetermined value.

10. An scanning light beam writing apparatus, comprising:

a scanning light beam which projects along a scan path having a start position and an end position on a writing plane;  
 a first detector positioned in said scan path producing a first output signal in response to said scanning light beam passing over said first detector;  
 a second detector positioned after said first detector in said scanning path for producing a second output signal in response to said scanning light beam passing over said second detector, said second detector being spaced a predetermined fixed distance from said first detector;  
 means for monitoring said first output signal produced by said first detector as said scanning light beam passes over said first detector;  
 means for noting a reference position when said first output signal reaches a predetermined value and generating a pulse signal

based on said reference position;  
 means for changing the power level of said scanning beam to a predetermined second level in response to said reference position;  
 means for measuring said second output signal produced by said second detector when said scanning light beam passes over said second detector;  
 means for comparing the value of said second signal of said second detector with respect to a predetermined reference value; and  
 means for adjusting the power level of said scanning light beam in accordance with said predetermined value.





**FIG. 2**







FIG. 3

**THIS PAGE BLANK (USPTO)**



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 014 145 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
31.10.2001 Bulletin 2001/44

(51) Int Cl.7: **G02B 26/12, G06K 15/12,  
H04N 1/04**

(43) Date of publication A2:  
28.06.2000 Bulletin 2000/26

(21) Application number: **99204236.6**

(22) Date of filing: **10.12.1999**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Hoeft, Jon L., Eastman Kodak Company  
Rochester, New York 14650-2201 (US)**

(30) Priority: **22.12.1998, US 218508**


(71) Applicant: **EASTMAN KODAK COMPANY  
Rochester, New York 14650 (US)**

(74) Representative:  
**Nunney, Ronald Frederick Adolphe et al  
Kodak Limited,  
Patents, W92-3A,  
Headstone Drive  
Harrow, Middlesex HA1 4TY (GB)**

(54) **Method and apparatus for determining the starting position and the power of a scanning light beam to be used in writing on a media**

(57) A method and apparatus for determining a line start writing position of a scanning light beam in a scanning light beam writing system. A first detector and a second detector are positioned in the scan path of the

scanning light beam for detection of the scanning light beam. The information obtained from the detector is used to determine the line start for commencing writing on a media and for monitoring and controlling the power level of the scanning light beam.



**FIG. 1**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 20 4236

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 4 386 272 A (CHECK JR FRANK T ET AL) 31 May 1983 (1983-05-31) * column 4, line 21 - line 26 * * column 5, line 27 - line 50; figure 1 *	1,3-8	G02B26/12 G06K15/12 H04N1/04
X	PATENT ABSTRACTS OF JAPAN vol. 007, no. 241 (P-232), 26 October 1983 (1983-10-26) & JP 58 127108 A (FUJI XEROX KK), 28 July 1983 (1983-07-28) * abstract; figures 5,6 *	1,3-8	
A	EP 0 773 461 A (TOKYO SHIBAURA ELECTRIC CO) 14 May 1997 (1997-05-14) * column 7, line 34 - line 50 * * column 8, line 46 - line 54 * * column 9, line 57 - line 59 * * column 12, line 36 - line 42 *	1-3,6-10	
A	GB 2 312 114 A (ICG LTD) 15 October 1997 (1997-10-15) * page 8, paragraph 2 - page 11, paragraph 4 * * page 12, paragraph 2 - page 13, line 1; claim 15; figure 2 *	1-10	TECHNICAL FIELDS SEARCHED (Int.Cl.7) G02B H04N G06K
A	PATENT ABSTRACTS OF JAPAN vol. 016, no. 457 (P-1426), 22 September 1992 (1992-09-22) & JP 04 162013 A (BROTHER IND LTD), 5 June 1992 (1992-06-05) * abstract; figure 1 *	1-10	
The present search report has been drawn up for all claims			
Place of search <b>MUNICH</b>		Date of completion of the search <b>27 August 2001</b>	Examiner <b>Besser, V</b>
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EP FORM 1303 (01.02.99)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 20 4236

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-08-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4386272 A	31-05-1983	US 4310757 A	12-01-1982
		US 4214157 A	22-07-1980
		US 4809021 A	28-02-1989
		CA 1145170 A	26-04-1983
		CA 1158464 A	13-12-1983
		CA 1164696 A	03-04-1984
		DE 2927101 A	17-01-1980
		DE 2954203 C	22-09-1988
		FR 2438315 A	30-04-1980
		GB 2027950 A,B	27-02-1980
		GB 2101360 A,B	12-01-1983
		GB 2096335 A,B	13-10-1982
		JP 55015197 A	02-02-1980
JP 58127108 A	28-07-1983	NONE	
EP 0773461 A	14-05-1997	US 5883385 A	16-03-1999
		CN 1150254 A,B	21-05-1997
		JP 9189873 A	22-07-1997
GB 2312114 A	15-10-1997	US 6084627 A	04-07-2000
JP 04162013 A	05-06-1992	JP 2956195 B	04-10-1999

LPO-CITM-P0459

For more details about this annex, see Official Journal of the European Patent Office, No. 12/82

**THIS PAGE BLANK (USPTO)**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**